

Inrico DR10 Gateway - LMR & PoC

HYBRID SYSTEM

Terminal Default Buttons



version 7.0

Guide

-  Short press
-  Long press
-  Rotate



Tested Accessories



GPSANT
GPS Antenna



4GAST
2G/3G/4G LTE
Cellular Antenna



PS-DR
Inrico DR10 Power
Adapter

Connection

Canada and US Version	GSM: B2,B5, WCDMA: B1, B2, B4, B5 FDD-LTE: B1, B2, B4, B5, B7, B12, B13, B17, B28A, B28B.
Wi-Fi	WIFI 2.4 G & 5G Dual Band
Navigation	GPS, AGPS
High Precision Positioning Module	PL05: MXT903A BDSGPS dual system sub-meter navigation and positioning module.

Hardware

CPU	MT6737
Memory	1GB (RAM) + 8GB (ROM)
SIM Card Slot	Dual Micro-SIM card
USB Ports	USB 2.0
Display	2.45 inch, IPS, G + F Single Touch screen

Physical

Dimension (H x W x D)	234 x 144 x 235mm
Weight	≈4.85KG
Working Temperature	-20°C ~ 80°C
Storage Temperature	-20°C ~ 60°C

LMR Specifications

Frequency	VHF (136-174MHz) / UHF (403-470MHz)
Output Power	VHF: 1-25 W; UHF: 1-25 W
Channel Spacing	12.5 khz, 20 khz, 25 khz